

MONTGOMERY WB Series CARRIAGES



Standard Equipment:

- Heavy wall tube carriage frame
- 12" all steel wheels
- 2½" square axles
- Tapered roller bearings in wheels
- Hydraulic dogs
- Hydraulic networks w/8 presets
- Ratchet style cable tightener
- Hydraulics mounted on carriage
- Reversible wear plates
- 20 HP pump package w/motor
- Replaceable dog bits
- Rack and pinion movement

SPECIFICATIONS	MODEL SIZE		
	WB36	WB40	WB44
Standard openings	36"	40"	44"
Standard Carriage Lengths	10'	15'	20'
Wheel centers	49 ³ / ₄ "	53 ³ / ₄ "	58 ³ / ₈ "
Dogs extended	3 ⁵ / ₈ "	3 ⁵ / ₈ "	3 ⁵ / ₈ "
Dogs retracted	5 ⁵ / ₈ "	5 ⁵ / ₈ "	5 ⁵ / ₈ "
Dog bit opening	26 ¹ / ₂ "	26 ¹ / ₂ "	26 ¹ / ₂ "
Overall width max. open	89"	93"	97 ⁵ / ₈ "
Overall width min. open	73"	77"	81 ⁵ / ₈ "

Add options to build your exact needs!

Options

- 0"-4" variable taper dual cyl.
- Variable tapers up to 12"
- Cant flipper Kickers
- Hammer Dog
- Push button lubrication
- 1" Thick dog bits
- Stainless steel wear plates and bits
- 2³/₈" set shaft

Heavier HD Series available with or without linear positioning!

MONTGOMERY MILL SUPPLIES, INC.

529 BROAD STREET EXTD.

DELTA, PA 17314

(717) 456-7008



AUTHORIZED DEALER